

X11-G2 动力套技术参数

动力套参数 All-in-One Thrust System Specification

产品型号	CM-X11-G2	最大拉力	32 kg (海平面高度)
Model		Max Thrust	32 kg (at sea level)
单轴推荐拉力	16.5 kg (海平面高度)	推荐拉力力效	7.5 g/W
Recommended takeoff weight per axis	16.5 kg (at sea level)	Efficiency of recommended takeoff weight	
适配锂电池	14S (LiPo)	额定电压	14S-54 V
Compatible lithium battery		Rated voltage	
电压范围	18-63 V	适用碳管直径	D45 mm
Input voltage		Tube outer diameter	
动力套重量 (含线、桨)	1980 g*	线材规格	电源线 : 12AWG 1050 mm* 信号线: 1090 mm*
Weight (with cable and propeller)		Cable specification	Power cable: 12AWG 1050 mm* Signal cable: 1090 mm*
适用环境温度	-20~50 °C	防尘防水等级	IPX6
Operating temperature		Ingress Protection	
额定输入功率	2200 W	额定输出功率	1870 W
Rated power input		Rated power output	
线序	黑-GND, 白-PWM; 红-CH, 灰-CL		
Pinout	Black-GND, White-PWM & Red-CH, Gray-CL		

电调技术参数 ESC Specification

产品型号	150A-FOC	通讯方式	Cyphal (UAVCAN)
Model		Communication protocol	
最大电流	150 A (3s)	持续电流	60 A
Peak current (3s)		Continuous current	
油门行程校准	不支持	双油门	PWM + CAN
Throttle range calibration	Not supported	Throttle Source	
PWM脉宽	1050-1950 µs	故障存储+日志	支持
Operating pulse width		Fault storage & Log	Supported

电机技术参数 Motor Specification

产品型号	11115-95KV	槽极数	36N40P
Model		Slot & Pole	
定子尺寸	111*15 mm	电机外直径	120.1 mm (风扇138 mm)
Stator diameter		Motor diameter	120.1 mm (Fan 138 mm)

桨叶参数 Propeller Specification

产品型号	43*14" (折叠桨)	总重量	427 g*
Model	43*14" (Folding propeller)	Total Weight	
主要材质	碳纤维增强尼龙复合材料	单片桨叶重量	146 g*
Material of blades	Carbon fibre-reinforced nylon composite material	Single blade weight	

*存在误差，以实物为准。
Subject to the actual product.