

RTF 4720-360KV



基础参数 Specification

产品型号	RTF 4720-300KV		
Model			
电机尺寸	Φ55.3*45.6	槽极数	18槽16极
Motor Size		Slot& Pole	18N16P
定子尺寸	Φ46.6*20	轴承型号	688ZZ
Stator Size		Bearing	
定子工艺	高品质矽钢片, 耐180°C高温涂覆	出轴轴径	Φ6mm
Stator process	High standard silicon steel sheet,180°C high temperature resistance paint-coat	Motor axle diameter	
漆包线等级	耐220°C高温 C级	出轴尺寸	22mm
Enamelled wire		Shaft Lenght	
桨夹安装孔螺纹	Φ12mm*2-M3	线圈绝缘测试	500V交流耐压测试
Fiber Screw Thread		Isolation test	500V AC high voltage resistance test
底座螺纹	Φ30mm*4-M4		
Screw Diameter / Thread			

技术参数 Specification

KV值	360	
KV		
额定电压	LiPo-8S	
Battery(LiPo)		
空载电流	3.6A/32V	
No-load current		
Rated power output	800W	
额定输出功率		
Maximum Current	86A/45s	
最大电流		
最大功率	2749W/45s	
Max power		
最大拉力	8.7kg	
Max thrust		
相间内阻	47mΩ	
Resistance		
出线规格	14AWG	
Wire Size		
出线长度	500mm	
Wire length		
电机重量(含线)	360g	
Weight (With wire)		