

X6SE-380KV 动力套技术参数

动力套参数 All-in-one thrust system specification

产品型号	CM-X6-SE-6208-380KV	最大拉力	5.5kg
Model		Max Thrust	
单轴推荐拉力	2kg	推荐拉力效率	8.4g/w
Recommended takeoff weight per axis		Efficiency of recommended takeoff weight	
电压范围	9-27V	额定电压	23V
Input voltage		Rated voltage	
适配锂电池	6S (LiPo)	适用碳管直径	25mm
Lithium compatible		Tube outer diameter	
动力套重量 (含线、桨)	348±5g	线材规格	电源线: 16AWG*560±10mm 信号线: 620±10mm
Weight (with cable and Props)		Cable specification	Power cable: 16AWG*560±10mm Signal cable: 620±10mm
适用环境温度	-20~50°C	防尘防水等级	IP43
Operating temperature		Ingress Protection	

电调技术参数 ESC specification

产品型号	60A-BLDC	通讯方式	UAVCAN
Model		Communication protocol	
电调尺寸	55mm*25mm (PCB)	重量 (不含线)	15g
ESC size		Weight (without cable)	
最大电流	60A (3s)	持续电流	30A
Peak current (3 seconds)		Continuous current	
油门行程校准	不支持	双油门	PWM+CAN
Throttle travel calibration	Nonsupport	Double throttle signal	
PWM脉宽	1100-1940µs	故障存储	支持
Operating pulse width		Failure storage	Support

电机技术参数 Motor specification

产品型号	6208-380KV	电机重量(含线)	172g
Model		Weight (with wire)	
电机外直径	68.7mm	槽极数	24N28P
Motor diameter		Slot& Pole	

桨叶参数 Propeller specification

产品型号	HF18*6.0"	单支重量	41g
Model		Weight	
主要材质	碳塑折叠桨	安装尺寸	D18-2*M3, 中心孔 D8
Material of Props	Carbon nylon folding Props	Mounting dimensions	D18-2*M3, centre hole D8