

XRotor-2207.5SL-1780KV

基础参数 Specification

产品型号	XRotor-2207.5SL-1780KV		
Model			
电机尺寸	Φ28*H19.9mm	槽极数	12槽14极
Motor Size		Slot& Pole	12N14P
定子尺寸	Φ22.5*7.6mm	轴承型号	MR105ZZ
Stator Size		Bearing	
定子工艺	0.2mm高品质矽钢片	出轴轴径	Φ5mm+M5
Stator process	High standard silicon steel sheet	Motor axle diameter	
漆包线等级	耐220℃高温 C级	电机安装孔尺寸	4×M3@Φ16
Enamelled wire		Motor mounting dimensions	
螺旋桨	GF51466三叶桨	GF51477三叶桨	
Propeller	HQ4.9x3.7x3三叶桨	HQ5.1x4x3三叶桨	

技术参数 Specification

KV值	1780
KV	
额定电压	LiPo-6S
Battery(LiPo)	
空载电流	2.7A
No-load current	
最大电流/A(非密闭环境温度 ≤25 ℃)	41A/3s
Maximum current (Non-hermetic Ambient Temperature ≤ 25℃)	
额定输出功率	130W
Rated power output	
最大功率	988W/3s
Max power	
最大拉力	1827g
Max thrust	
相间内阻	76mΩ
Resistance	
出线规格	20AWG
Wire Size	
出线长度	150mm
Wire length	
电机重量(含线)	38g
Weight (With wire)	