

RTF 2810-1100KV



基础参数 Specification

产品型号	RTF 2810-1100KV		
Model			
电机尺寸	Φ34*23.5mm	槽极数	12槽14极
Motor Size		Slot& Pole	12N14P
定子尺寸	Φ28*10mm	轴承型号	685ZZ
Stator Size		Bearing	
定子工艺	高品质矽钢片, 耐180°C高温涂覆	出轴轴径	Φ5mm
Stator process	High standard silicon steel sheet, 180°C high temperature resistance paint-coat	Motor axle diameter	
漆包线等级	耐220°C高温 C级	出轴尺寸	15mm
Enamelled wire		Shaft Lenght	
线圈绝缘测试	500V交流耐压测试	电机安装孔尺寸	Φ19mm-4*M3
Isolation test	500V AC high voltage resistance test	Motor mounting dimensions	

技术参数 Specification

KV值	1100
KV	
额定电压	LiPo-6S
Battery(LiPo)	
空载电流	2.0A
No-load current	
最大电流/A(非密闭环境温度 ≤25 °C)	53A/12s
Maximum current (Non-hermetic Ambient Temperature ≤ 25°C)	
额定输出功率	230W
Rated power output	
最大功率	1263W/12s
Max power	
最大拉力	3.3kg
Max thrust	
相间内阻	48mΩ
Resistance	
出线规格	18AWG
Wire Size	
出线长度	200mm
Wire length	
电机重量(含线)	72g
Weight (With wire)	