

RTF 4720-300KV



基础参数 Specification

产品型号	RTF 4720-300KV		
Model			
电机尺寸	Φ55.3*45.6	槽极数	18槽16极
Motor Size		Slot& Pole	18N16P
定子尺寸	Φ46.6*20	轴承型号	688ZZ
Stator Size		Bearing	
定子工艺	高品质矽钢片, 耐180°C高温涂覆	出轴轴径	Φ6mm
Stator process	High standard silicon steel sheet,180°C high temperature resistance paint-coat	Motor axle diameter	
漆包线等级	耐220°C高温 C级	出轴尺寸	22mm
Enamelled wire		Shaft Lenght	
桨夹安装孔螺纹	Φ12mm*2-M3	线圈绝缘测试	500V交流耐压测试
Fiber Screw Thread		Isolation test	500V AC high voltage resistance test
底座螺纹	Φ30mm*4-M4		
Screw Diameter / Thread			

技术参数 Specification

KV值	300
KV	
额定电压	LiPo-12S
Battery(LiPo)	
空载电流	2.66A/44.4V
No-load current	
Rated power output	960W
额定输出功率	
最大电流/A(非密闭环境温度 ≤25 °C)	68A/9s
Maximum current (Non-hermetic Ambient Temperature ≤ 25°C)	
最大功率	2195W/9s
Max power	
最大拉力	8.2kg
Max thrust	
相间内阻	53.92mΩ
Resistance	
出线规格	直出线
Wire Size	
出线长度	500mm
Wire length	
电机重量(含线)	347g
Weight (With wire)	