

V6215

基础参数 Specification I

产品型号 Model	V6215-210KV	防尘防水等级 Protection level	IPX5
电机尺寸 Motor Size	Φ68.7*H39.3mm	槽极数 Slot& Pole	24槽28极 24N28P
定子尺寸 Stator Size	Φ62*H15mm	电机整体动平衡标准 Dynamic balance	≤10mg
定子工艺 Stator process	高品质硅钢片，防锈处理，耐180℃高温涂覆 High standard silicon steel sheet, rust proof, 180℃ high temperature resistance paint-coat	轴承型号 Bearing	高品质防水轴承 Water proof bearing
漆包线等级 Enamelled wire	200℃	出轴轴径 Motor axle diameter	Φ6mm
磁铁等级 Magnet	150℃	桨叶安装孔尺寸 Props mounting dimensions	4*M3@D12mm, 4*M3@D18mm
线圈绝缘测试 Isolation test	500V交流耐压测试 500V AC high voltage resistance test	电机安装孔尺寸 Motor mounting dimensions	4*M4@D25mm
额定输入功率 Rated power input	975W	额定输出功率 Rated power output	806W

技术参数 Specification II

KV值 KV	210KV
额定电压 Battery(LiPo)	LiPo-12S
空载电流 No-load current	2.6A
最大电流/A(非密闭环境温度 ≤25 °C) Maximum current (Non-hermetic Ambient Temperature ≤ 25°C)	81A
最大功率 Max power	3733W
最大拉力 Max thrust	13.8kg
相间内阻 Resistance	48.2mΩ
出线规格 Wire Size	14AWG
出线长度 Wire length	600mm
电机重量(含线) Weight (With wire)	354g