

V5212

基础参数 Specification I

产品型号 Model	V5212-275KV	防尘防水等级 Protection level	IPX5
电机尺寸 Motor Size	Φ58*H37.2 mm	槽极数 Slot& Pole	24槽28极 24N28P
定子尺寸 Stator Size	Φ52*H12 mm	电机整体动平衡标准 Dynamic balance	≤10mg
定子工艺 Stator process	高品质硅钢片, 防锈处理, 耐180℃高温涂覆 High standard silicon steel sheet, rust proof, 180℃ high temperature resistance paint-coat	轴承型号 Bearing	高品质防水轴承 Water proof bearing
漆包线等级 Enamelled wire	200℃	出轴轴径 Motor axle diameter	Φ4mm
磁铁等级 Magnet	150℃	桨叶安装孔尺寸 Props mounting dimensions	4*M3@D12mm, 4*M4@D18 mm
线圈绝缘测试 Isolation test	500V交流耐压测试 500V AC high voltage resistance test	电机安装孔尺寸 Motor mounting dimensions	4*M3@D25 mm
额定输出功率 (最大持续功率) Rated output power (Max continuous)	574 W		

技术参数 Specification II

KV值 KV	275 KV
额定电压 Battery(LiPo)	LiPo-12S
空载电流 No-load current	2.25 A
最大电流/A(非密闭环境温度 ≤25 °C) Maximum current (Non-hermetic Ambient Temperature ≤ 25°C)	53 A
最大拉力 Max thrust	9.1 kg
相间内阻 Resistance	64 mΩ
出线规格 Wire Size	16 AWG
出线长度 Wire length	600 mm
电机重量(含线) Weight (With cable)	248 g