

RTF 5320-350KV



基础参数 Specification

产品型号	RTF 5320-350KV-BLACK-V1		
Model			
电机尺寸	Φ62.1*71.1	槽极数	12槽14极
Motor size		Slot& Pole	12N14P
定子尺寸	Φ52.9*20	轴承型号	688ZZ、698ZZ
Stator size		Bearing	
定子工艺	高品质矽钢片，防锈处理，耐180℃高温涂覆	出轴轴径	Φ6mm
Stator process	High standard silicon steel sheet, rust proof, 180℃ high temperature resistance paint-coat	Motor axle diameter	
漆包线等级	耐200℃高温 C级	桨叶安装孔尺寸	Φ12mm-2*M3&Φ15mm-2*M3
Enamelled wire	220℃ high temperature resistant, C class insulatic	Props mounting dimensions	
线圈绝缘测试	500V交流耐压测试	电机安装孔尺寸	Φ30mm-4*M4
Isolation test	500V AC high voltage resistance test	Motor mounting dimensions	

技术参数 Specification

KV值	350
KV	
额定电压	LiPo-8S
Battery(LiPo)	
空载电流	3.35A
No-load current	
最大电流/A(非密闭环境温度 ≤25 ℃)	105A/57s
Maximum current (Non-hermetic Ambient Temperature ≤ 25℃)	
额定输出功率	1520W
Rated power output	
最大功率	3340W/57s
Max power	
最大拉力	11.2kg
Max thrust	
相间内阻	26mΩ
Resistance	
出线规格	14AWG
Wire size	
出线长度	620mm
Wire length	
电机重量(含线)	488g
Weight(With wire)	