

H15MD 100 28S 共轴动力套技术参数

H15MD 100 28S Coaxial Propulsion System Specification

动力套参数 All-in-One Thrust System Specification			
产品型号 Model	H15MD 100 28S	适配锂电池 Compatible Lithium Battery	LiPo-28S
额定电压 Rated Voltage	28S-108 V	电压范围 Input Voltage	36~130 V
推荐单轴起飞拉力 Recommended Single-Axis Takeoff Thrust	95~105 kg (海平面、环境温度25℃) 95~105 kg (sea level, ambient temperature 25℃)	单轴100kg拉力力效 Efficiency when single-axis thrust at 100kg	6.5 g/W
适用海拔 Operating Altitude	0~5000 m (不同环境温度下, 海拔每升高 1500m, 单轴起飞重量下调 5%~10%) (For every 1,500 m increase in altitude, the single-axis takeoff weight must be derated by 5% to 10% under different ambient temperatures.)	最大允许飞行速度 (无风) Max Allowable Flight Speed (calm air)	15 m/s
适用环境温度 Operating Temperature	-40~60 ℃	防护等级 Ingress Protection	IPX6
动力套重量 (含线、含桨) Weight (with cable and propeller)	19170±300 g	适用碳管直径 Tube Outer Diameter	80 mm (壁厚推荐4轴3mm, 6轴/8轴5mm) 80 mm (Thickness: 3mm for 4-axis, 5mm for 6-axis and 8-axis.)
线材规格 Cable Specification	电源线: 7AWG 2700±50 mm 信号线: 2900±50 mm Power Cable: 7AWG 2700±50 mm Signal Cable: 2900±50 mm	额定输出功率 (最大持续功率) Rated Output Power (max continuous)	20500 W
线序 Pinout	黑-GND, 白-PWM; 黄-GND, 灰-CANH, 绿-CANL Black-GND, White-PWM, Yellow-GND, Gray-CANH, Green-CANL		

*本产品标注的拉力性能参数, 均基于好盈封闭实验室 (海平面, 环境温度25℃) 测试平台独立测试获得。

*在实际飞行工况中, 受飞控系统适配程度、整机构型布局差异、重心配置状态等多重因素影响, 各轴电机的实际输出功率并非完全均等, 存在分配差异。产品选型时请充分考量上述工况偏差, 建议以官方的推荐单轴起飞拉力参数作为选型依据。

*The thrust performance parameters of this product are independently measured on the test bench in Hobbywing's enclosed laboratory (sea level, ambient temperature 25℃).

*In real flight scenarios, multiple factors such as flight controller matching, airframe layout differences and center-of-gravity configuration can lead to unequal actual output power for motors on each axis, resulting in power distribution imbalance. Fully account for such operational deviations when selecting products; use the official recommended single-axis takeoff thrust parameters as the selection reference.

以下测试平台指好盈科技内部的拉力台架测试平台。此数据是在单动力台架测得的单轴气动理想状态, 用于供专业级用户在较为特殊整机气动设计时参考。

*在实际飞行工况中, 受飞控系统适配程度、整机构型布局差异、重心配置状态等多重因素影响, 各轴电机的实际输出功率并非完全均等, 存在分配差异。产品选型时请充分考量上述工况偏差, 建议以官方的推荐单轴起飞拉力参数作为选型依据。

*The thrust performance parameters of this product are independently measured on the test bench in Hobbywing's enclosed laboratory (sea level, ambient temperature 25℃).

*In real flight scenarios, multiple factors such as flight controller matching, airframe layout differences and center-of-gravity configuration can lead to unequal actual output power for motors on each axis, resulting in power distribution imbalance. Fully account for such operational deviations when selecting products; use the official recommended single-axis takeoff thrust parameters as the selection reference.

*The test bench referred to below is Hobbywing's internal thrust test bench. All the data is obtained from single propulsion system test bench, under ideal single-axis aerodynamic conditions, only as reference for professional users dealing with special aerodynamic design of drone.

*After the propulsion system is installed on the drone, there will be aerodynamic losses due to the aerodynamic drag of the entire drone and aerodynamic interference between rotors, and the aerodynamic loss varies with different configurations. Therefore, the actual thrust output will be slightly lower than the bench test result at same RPM. That's why the recommended single-axis takeoff thrust is lower than the test bench continuous rated thrust. This recommended value was measured from actual flight tests of our 4-axis, 8-rotor model with a takeoff weight of 400kg, cruising speed of 15m/s, and ambient temperature of 25℃ The final configuration shall be determined by the specific model and operating conditions.

测试平台持续额定拉力 Test Bench Continuous Rated Thrust	130 kg (海平面、环境温度25℃) 130 kg (sea level, ambient temperature 25℃)	测试平台最大拉力 Test Bench Max Thrust	215 kg (海平面高度, 环境温度25℃) 215 kg (sea level, ambient temperature 25℃)
--	---	-----------------------------------	--

电调技术参数 ESC Specification

电压范围 Input Voltage	36~130 V	通讯方式 Communication Protocol	HWCAN / DroneCAN
电调尺寸 ESC Size	203*95*56 mm	重量 (含线) Weight (with cable)	2030±100 g
最大电流 (3s) Peak Current (3s)	300A@108V	持续电流 Continuous Current	130A@108V
防护等级 Ingress Protection	IP67	油门源 Throttle Source	PWM+CAN
PWM脉宽 Operating Pulse Width	1100~1940 μs	黑匣子功能 Black Box	故障数据 + 1~24小时日志 Fault data and 1~24-hour log
油门行程校准 Throttle Range Calibration	固化不可校准, 软件可修改范围 Solidified and cannot be calibrated (can be changed via DataLink software)		

电机技术参数 Motor Specification

KV值 KV	32 KV	槽极数 Slot & Pole	36槽32极 36N32P
电机外径 Motor Diameter	Φ167.1 mm	电机重量 (含线) Weight (with cable)	4630±100 g
防护等级 Ingress Protection	IPX6	桨叶安装尺寸 Propeller Mounting Dimensions	D49-4*M8

桨叶参数 Propeller Specification

产品型号 Model	MFC 73x25	重量 (含桨夹) Weight (Including propeller adapter)	1900±30 g
主要材质 Material of Propeller	碳纤维复合材料 Carbon fiber composite material	安装尺寸 Mounting Dimensions	D49-4*M8, 中心孔D16 D49-4*M8, centre hole D16
安装螺丝锁紧扭矩 Mounting Screw Tightening Torque	18 N·m	适用海拔 Operating Altitude	0~3000 m
产品型号 Model	MFC 73x34	重量 (含桨夹) Weight (Including propeller adapter)	1900±30 g
主要材质 Material of Propeller	碳纤维复合材料 Carbon fiber composite material	安装尺寸 Mounting Dimensions	D49-4*M8, 中心孔D16 D49-4*M8, centre hole D16
安装螺丝锁紧扭矩 Mounting Screw Tightening Torque	18 N·m	适用海拔 Operating Altitude	2500~5000 m