X6 Plus G2 动力套技术参数

X6 Plus G2 Propulsion System Specification

动力套参数 All-in-One Thrust System Specification

产品型号 Model	X6 Plus G2	适配锂电池 Compatible Lithium Battery	LiPo-12~14S
额定电压 Rated Voltage	14S-54V / 12S-48V	电压范围 Input Voltage	18~63 V
额定拉力 Rated Thrust	4~6 kg（海平面、环境温度25℃） 4~6 kg (sea level, ambient temperature 25℃)	最大拉力 Max Thrust	12.5 kg（海平面、环境温度25℃） 12.5 kg (sea level, ambient temperature 25℃)
额定拉力力效 Efficiency at Rated Trust	8.6~7.1 g/W	适用海拔 Operating Altitude	0~2000 m （不同环境温度下，海拔每升高 1500m，单轴起飞重量下调 5%~10%） (For every 1,500 m increase in altitude, the single-axis takeoff weight must be derated by 5% to 10% under different ambient temperatures.)
最大允许飞行速度（无风） Max Allowable Flight Speed (calm air)	13.8 m/s	适用环境温度 Operating Temperature	-20~50 ℃
防护等级 Ingress Protection	IPX6	动力套重量（含线、不含桨） Weight (with cable, without propeller)	641 g
线材规格 Cable Specification	电源线：14AWG 870±10 mm 信号线：1000±10 mm Power Cable: 14AWG 870±10 mm Signal Cable: 1000±10 mm	适用碳管直径 Tube Outer Diameter	30 mm
额定转速 Rated RPM	4000 rpm	额定输出功率（最大持续功率） Rated Output Power (max continuous)	0.7 kW
线序 Pinout	黑-GND，白-PWM；黄-GND, 灰-CANH，绿-CANL Black-GND, White-PWM & Yellow-GND, Gray-CANH, Green-CANL	额定功率密度 Rated Power Density	1.9 kW/kg

*本产品标注的拉力性能参数，均基于好盈封闭实验室（海平面，环境温度25℃）测试平台独立测试获得。
*在实际飞行工况中，受飞控系统适配程度、整机构型布局差异、重心配置状态等多重因素影响，各轴电机的实际输出功率并非完全均等，存在分配差异。产品选型时请充分考量上述工况偏差，建议以官方推荐的额定拉力参数作为选型依据。
*The thrust performance parameters of this product are independently measured on the test bench in Hobbywing's enclosed laboratory (sea level, ambient temperature 25℃).
*In real flight scenarios, multiple factors such as flight controller matching, differences in airframe configuration and layout, and center-of-gravity configuration can lead to unequal actual output power for motors on each axis, resulting in power distribution differences. Fully account for such operational deviations when selecting products; use the official rated thrust parameters as the selection reference.

电调技术参数 ESC Specification

电压范围 Input Voltage	18~63 V	通讯方式 Communication Protocol	HWCAN / DroneCAN
最大电流（3s） Peak Current (3s)	80 A @54V	持续电流 Continuous Current	25 A @54V
防护等级 Ingress Protection	IPX6	油门源 Throttle Source	PWM+CAN
PWM脉宽 Operating Pulse Width	1050~1950 μs	黑匣子功能 Black Box	故障数据 + 1~24小时日志 Fault data and 1~24-hour log
油门行程校准 Throttle Range Calibration	固化不可校准，软件可修改范围 Solidified and cannot be calibrated (can be changed via DataLink software)		

电机技术参数 Motor Specification

KV值 KV	150 KV	槽极数 Slot & Pole	28槽24极 28N24P
电机外径 Motor Diameter	68.9 mm	电机重量 (含线) Weight (with cable)	370 g
防护等级 Ingress Protection	IPX6	桨叶安装尺寸 Propeller Mounting Dimensions	D20-8*M3，中心孔D8 D20-8*M3, centre hole D8

桨叶参数 Propeller Specification

产品型号 Model	MFP 24x8.0	重量 Weight	107 g
主要材质 Material of Propeller	碳纤维增强尼龙复合材料 Carbon fibre-reinforced nylon composite material	安装尺寸 Mounting Dimensions	D20-4*M3.2，中心孔D8 D20-4*M3.2, centre hole D8
安装螺丝锁紧扭矩 Mounting Screw Tightening Torque	1~1.2 N·m	适用海拔 Operating Altitude	0~2000 m
桨根到桨尖的距离 Blade Length (end of root to tip)	294.5 mm		